

NTLE-860

4' Track Pack with (3) MAY LED Track Heads

Source: 10W LED per head

Up to 850lm per head

Type

Project

Catalog No.

Notes

PRODUCT DESCRIPTION

Track pack comes complete and ready to install with mounting hardware and track heads. Components includes: (1) 4' single circuit track, (2) end caps, (1) floating canopy feed and (3) MAY LED track heads. The utilitarian style fits almost any design criteria.

FEATURES

- Over 75% energy savings when compared to incandescent
- 4' Track Pack includes all hardware and ready to install
- 2700K, 3000K, 3500K or 4000K at 90 CRI
- Narrow flood beam spread
- Available in black or white finishes
- Up to 850lm / 10W LED output per head
- Easily to longer lengths or additional track heads
- Perfect for multi family homes or apartments
- Dimmable

CONSTRUCTION

Housing: Die-cast aluminum construction dissipates heat for longer life.

Adjustability: 315° horizontal and 359° vertical adjustment

ELECTRICAL

Input Voltage: 120V

Lumens / Wattage Per Head: Up to 850lm / 10W

Color Temperature: 2700K 3000K, 3500K or 4000K

Color Rendering Index: 90+ CRI

Beam Spread: 34° Narrow Flood

Lifetime: 50,000 hours @ L70

Dimming: Triac or ELV

[Click Here](#) or check complete dimmer list at www.NoraLighting.com in the "Compatibility" page under "Resources" tab

One / Two Circuit Conversion: Positive contact (opposite neutral and ground contacts) is preset to "down" position at factory, but may be raised to the higher position to install onto the second circuit of Nora Lighting NT-2300 series two-circuit track.

LABELS AND LISTINGS

- cETLus Listed for dry locations
- ENERGY STAR certified
- [5-Year Limited Warranty](#)
- FCC compliant



Performance Data Per Head

Part Number	Lumens	CCT
NTLE-860L927	753lm	2700K
NTLE-860L930	801lm	3000K
NTLE-860L935	848lm	3500K
NTLE-860L940	866lm	4000K

Delivered lumens will vary depending on finish

PRODUCT IMAGE



NTLE-860B



NTLE-860W

4' Track Pack with (3) MAY LED Track Heads

Series	Color Temperature	Finish
NTLE-860L = 4' Track Pack with (3) MAY LED Track Heads	927 = 2700K	10B = Black
	930 = 3000K	10W = White
	935 = 3500K	
	940 = 4000K	

Example: **NTLE-860L92710B** = 4' Track Pack with (3) MAY LED Track Heads, 2700K, Black Finish

PHOTOMETRICS

MAY LED Track Head

Type


Project

Catalog No.

Notes

Test Information

Test Number: NTT11022R2
 Part Number: NTE-860L927M10
 Beam Spread: 34° Narrow Flood
 Lumens: 753lm
 Wattage: 9.3W
 Efficacy: 81lpw
 CCT / CRI: 2700K / 90 CRI
 Spacing Criteria (0°-180°): 0.58
 Spacing Criteria (90°-270°): 0.58



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	112fc	2'-6"
6'	49.7fc	3'-8"
8'	27.9fc	4'-11"
10'	17.9fc	6'-2"
12'	12.4fc	7'-5"

Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	629	83.6
0-40	697	92.6
0-60	732	97.3
0-90	743	98.7
90-180	10	1.3
0-180	753	100

Candela Table

Vertical Angles	Candela
0	1788
5	1706
15	1066
25	394
35	101
45	27

Test Information

Test Number: NTT11023R1
 Part Number: NTE-860L930M10
 Beam Spread: 34° Narrow Flood
 Lumens: 801lm
 Wattage: 9.42W
 Efficacy: 85lpw
 CCT / CRI: 3000K / 90 CRI
 Spacing Criteria (0°-180°): 0.58
 Spacing Criteria (90°-270°): 0.58



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	119fc	2'-6"
6'	52.9fc	3'-8"
8'	29.8fc	5'
10'	19fc	6'-2"
12'	13.2fc	7'-6"

Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	675	84.3
0-40	746	93.2
0-60	781	97.5
0-90	790	98.7
90-180	11	1.3
0-180	801	100

Candela Table

Vertical Angles	Candela
0	1904
5	1795
15	1133
25	440
35	105
45	226

Test Information

Test Number: NTT11024R2
 Part Number: NTE-860L935M10
 Beam Spread: 34° Narrow Flood
 Lumens: 848lm
 Wattage: 9.47W
 Efficacy: 90lpw
 CCT / CRI: 3500K / 90 CRI
 Spacing Criteria (0°-180°): 0.58
 Spacing Criteria (90°-270°): 0.58



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	125fc	2'-6"
6'	55.6fc	3'-8"
8'	31.3fc	5'
10'	20fc	6'-2"
12'	13.9fc	7'-6"

Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	710	83.7
0-40	787	92.8
0-60	826	97.4
0-90	837	98.6
90-180	12	1.4
0-180	848	100

Candela Table

Vertical Angles	Candela
0	2002
5	1904
15	1200
25	454
35	116
45	29

Test Information

Test Number: NTT11025R2
 Part Number: NTE-860L940M10
 Beam Spread: 34° Narrow Flood
 Lumens: 866lm
 Wattage: 9.58W
 Efficacy: 90lpw
 CCT / CRI: 4000K / 90 CRI
 Spacing Criteria (0°-180°): 0.58
 Spacing Criteria (90°-270°): 0.58



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	126fc	2'-6"
6'	56.2fc	3'-10"
8'	31.6fc	5'
10'	20.2fc	6'-4"
12'	14fc	7'-6"

Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	725	83.7
0-40	803	92.7
0-60	842	97.2
0-90	853	98.5
90-180	13	1.5
0-180	866	100

Candela Table

Vertical Angles	Candela
0	2023
5	1927
15	1220
25	470
35	117
45	29