

NTP-31

6" BR/PAR30 Phenolic (Plastic) Stepped Baffle with White Plastic Ring

Type _____

Project _____

Catalog No. _____

Notes _____

FEATURES

Trim: Precision spun 0.040 plastic with deep grooves to reduce aperture glare and plastic trim ring. Non-reflective painted finishes. Trim may also be used with custom combination of ring finishes.

Mounting: Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86). Remove socket from socket plate within housing (if applicable), and mount lamp into gimbal ring.

COMPATIBLE HOUSINGS

Compatible with line voltage housings. See individual specification sheets for more information.

LAMP

· 50W BR/PAR30 Maximum (NH-26Q; NH-26QNB; NHIC-17/100DWQA; NHIC-17QAT; NHIC-17QNBAT; NHR-26Q; NHRIC-17QAT; NHRIC-17QNBAT)

LABELS AND LISTINGS

· cULus Listed for Damp Location when used with compatible housing.



PRODUCT IMAGES & DIMENSIONS



6" BR/PAR30 Phenolic (Plastic) Stepped Baffle with White Plastic Ring

Catalog No. _____

NTP-31 = White Phenolic Stepped Baffle with White Plastic Ring

Compatible Housings

Catalog No. _____

NH-26Q = Non-IC New Construction / 50W max
NH-26QNB = Non-IC Remodel, No Bracket / 50W max
NHIC-17/100DWQA = IC Air-Tight Double Wall / 50W max
NHIC-17QAT = C Air-Tight New Construction / 50W max
NHIC-17QNBAT = IC Air-Tight New Construction, No Bracket / 50W max
NHR-26Q = Non-IC Remodel / 50W max
NHRIC-17QAT = IC Air-Tight Remodel / 50W max
NHRIC-17QNBAT = IC Air-Tight Remodel, No Bracket / 50W max

Example: **NTP-31** = White Phenolic Stepped Baffle with White Plastic Ring